



800X1200MM OUTDOOR 3D DISPLAY

Pixel Pitch	4.16mm	5mm	6.25mm	8.33mm	10mm
Pixel Density(dot per sqm)	57,600	40,000	25,600	14,400	10,000
Pixel LED	SMD1921	SMD1921	SMD2727	SMD2727	SMD2727
Module Resolution(WxH)	96 x 72	80 x 60	64 x 48	48 x 36	40 x 30
Module Size(WxH)	400mm x 300mm				
Panel Resolution(WxH)	192 x 288	160 x 240	128 x 192	96 x 144	80 x 120
Panel Dimensions(WxHxD)	800mm x 1200mm x 98mm				
Weight Per Panel	28KG				
Panel Material	Aluminum				
Brightness	6000 nits	6000 nits	6500 nits	6500 nits	6500 nits
Viewing Angle	Horizontal 160°; Vertical 140°				
Gray Scale	12 bit to 16 bit				
Refresh Rate	>1920 Hz				
IP Rating	IP65 front and rear				
Color Temperature	3200-9300K(optional)				
Input Power Source	AC110-220V; 50/60Hz				
Average Power Consumption	240W/sqm				
Maximum Power Consumption	750W/sqm				
Operation Temperature	-20°C to +50°C				
Relative Humidity	10%-90%RH				
Serviceability	Front and rear access				